

Power Resistor, Thick Film Technology




FEATURES

- 50 Watt at 25 °C Heatsink Mounted
- Adjusted by sand trimming
- Leaded or surface mount versions
- High power to size ratio
- Non inductive element



Because of the knowledge and experience in Thick Film technology, Vishay Sfernice has been able to develop a high power resistor in a TO 220 package called RTO 50. The special design of this component allows the dissipation of 50 W when mounted on a heatsink. The ohmic value is adjusted by sand trimming. This process does not generate hot spots as in laser trimming, which could lead to microcracks on each side of the curve. This process improves the reliability and the stability of the resistor and at the same time gives a good overload capability.

DIMENSIONS in millimeters



• Tolerance unless otherwise specified: ± 0.4 mm

• Only for RTO 50 version C = during surface mount soldering, the soldering temperature profile must not cause the metal tab of this device to exceed 220 °C.

MECHANICAL SPECIFICATIONS

Mechanical Protection	Molded
Resistive Element	Thick Film
Connections	Tinned copper alloy
Weight	2 g max.

DIMENSIONS

Standard Package	TO 220 Insulated Case
------------------	--------------------------

ENVIRONMENTAL SPECIFICATIONS

Temperature Range	- 55 °C to + 155 °C
Climatic Category	55/155/156
Sealing	Sealed container Solder immersion

ELECTRICAL SPECIFICATIONS

Resistance Range	0.010 Ω to 1 M Ω serie E24
Tolerances Standard	± 1 % to ± 10 %
Dissipation and Associated	Onto a heatsink
Thermal Resistance and Nominal Power	50 W at + 25 °C R_{TH} (j-c): 2.6 °C/W free air: 2.25 W at + 25 °C
Temperature Coefficient	See Performance table
Standard	± 150 ppm/°C
Limiting Element Voltage	300 V
Dielectric Strength MIL STD 202 (301)	2000 V _{RMS} - 1 Minute - 10mA Max
Insulation Resistance	$\geq 10^6$ M Ω
Inductance	≤ 0.1 μ H
Critical Resistance	1.8 k Ω



PERFORMANCE		
TESTS	CONDITIONS	TYPICAL DRIFTS
Momentary Overload Us < 1.5 UL	NF EN 140 000 2 Pr/5 s	± (0.25 % + 0.05 Ω)
Rapid Temperature Change 5 cycles - 55 °C to + 155 °C	NF EN 140 000 CEI 68214 Tests Na	± (0.5 % + 0.05 Ω)
Load Life	NF EN 140 000 Pr at + 25 °C, 1000 hrs. CEI 115_1	± (1 % + 0.05 Ω)
Humidity (Steady State) Method 103 B Cond. D	MIL STD 202	± (0.5 % + 0.05 Ω)
Vibration Method 204 Cond. D	MIL STD 202	± (0.2 % + 0.05 Ω)
Terminal Strength	MIL STD 202	± (0.2 % + 0.05 Ω)

SPECIAL FEATURES				
Resistance Values	≥ 0.010 Ω	≥ 0.015 Ω	≥ 0.1 Ω	≥ 0.5 Ω
Tolerances	± 1 % at ± 10 %			
Temperature Coefficient	Standard ± 900 ppm/°C	± 700 ppm/°C	± 250 ppm/°C	± 150 ppm/°C

CHOICE OF THE HEATSINK

The user must choose according to the working conditions of the component (power, room temperature).

Maximum working temperature must not exceed 155 °C. The dissipated power is simply calculated by the following ratio:

$$P = \frac{\Delta T}{[R_{TH} (j-c) + R_{TH} (c-a)]} \quad (1)$$

P: expressed in W

T: difference between maximum working temperature and room temperature

R_{TH}: (j-c): thermal resistance value measured between resistive layer and outer side of the resistor. It is the thermal resistance of the component: (Special Features Table)

R_{TH}: (c-a): thermal resistance value measured between outer side of the resistor and room temperature. It is the thermal resistance of the heatsink itself (type, shape) and the quality of the fastening device

Example:

R_{TH}: (c-a) for RTO 50 power rating 13 W at ambient temperature + 30 °C

Thermal resistance R_{TH} (j-c): 26 °C/W

Considering equation (1) we have:

$$\Delta T \leq 155 \text{ °C} - 30 \text{ °C} \leq 125 \text{ °C}$$

$$R_{TH} (j-c) + R_{TH} (c-a) = \frac{\Delta T}{P} = \frac{125}{13} = 9.6 \text{ °C/W}$$


$$R_{TH} (c-a) \leq 9.6 \text{ °C/W} - 2.6 \text{ °C/W} \leq 7 \text{ °C/W}$$



OVERLOADS


The applied voltage must always be lower than the maximum overload voltage of 450 V.
The values indicated on the graph below are applicable to resistors in air or mounted onto a heatsink.

ENERGY CURVE



POWER RATING CHART

The temperature of the heatsink should be maintained within the limits specified.
To improve the thermal conductivity, surfaces in contact should be coated with a silicone grease and the torque applied on the screw for tightening should be around 1 Nm.



MARKING

Model, Style, Resistance Value (in Ω), Tolerance (in %), Manufacturing Date, VISHAY trademark.

PACKAGING							
Tube of 50 units							

ORDERING INFORMATION							
RTO	50	F	100K	1 %	xxx	TU50	e1
MODEL	STYLE	CONNECTIONS	RESISTANCE VALUE	TOLERANCE	CUSTOM DESIGN	PACKAGING	LEAD (Pb)-free
		F: Radial Leads C: Surface Mount		± 1% ± 2% ± 5% ± 10%	Optional on request: special TCR, shape etc.		

SAP PART NUMBERING GUIDELINES							
RTO	050	F	1000L	F	T	E1	
MODEL	STYLE	CONNECTIONS	RESISTANCE VALUE	TOLERANCE	PACKAGING	LEAD (Pb)-free	



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.